

DAFTAR REFERENSI

- [1] Schmit R.O. 1986. Multiple emitter location and signal parameter estimation. IEEE Trans. Antenna propagation. Vol AP No 34 : 276-280.
- [2] Roy R and T.kailath. 1989. ESPRIT-Estimation of signal parameters via rotational invariance techniques. IEEE Trans. Acoust. Speech. Signal Processing. Vol 37 No 7 : 984-995
- [3] Taem N and H.M.Kwon. 2005. Azimuth and elevation angle estimation with no failure and no eigen decomposition. IEEE Trans. Vol 86 : 8-16
- [4] Marcos S, A. Marsal, M. Benidir. 1995. The propagator method for source bearing estimation. Signal Procesing. Vol 42 : 121-138
- [5] <https://yasdinulhuda.wordpress.com/2009/04/29/antenna/> (diakses tanggal 6 september 2016)
- [6] http://www.byteboss.com/view.aspx?id=3483011&name=compressive-sensing-untuk-direction-of-arrival-estimation_seminar_mingguan2(diakses tanggal 6 september 2016)
- [7] <http://elib.unikom.ac.id/files/disk1/543/jbptunikompp-gdl-iryamannim-27128-5-iryaman-i.pdf> (diakses tanggal 6 september 2016)
- [8] <http://www.comm.utoronto.ca/~rsadve/Notes/DOA.pdf> (diakses tanggal 17 juli 2016)
- [9] <http://mlaiq.blogspot.co.id/2011/07/antenna-directional-omnidirectional.html> (diakses tanggal 17 juli 2016)
- [10] L Lutaο, J Qingbo, J Yilin. 2011. Improved Fast DOA Estimation Based on Propagator Method. Xi'an : APSIPA ASC
- [11] X Zhang, L Jianfeng, Xu Lingyun. 2011. Novel two-dimensional DOA estimation with L-shaped array. China : SPRINGER