

DAFTAR PUSTAKA

- [1] Alabi, P.D., 2006, *Time Development of Local Scour at Bridge Pier Fitted With a Collar*, Thesis, University of Saskatchewan, Saskatoon.
- [2] Chow, V.T., 1989, *Open-Channel Hydraulic*, Erlangga, Bandung.
- [3] Hanwar, S., 1999, *Gerusan Lokal di Sekitar Abutmen Jembatan*, Tesis S2 Program Pasca Sarjana UGM, Yogyakarta.
- [4] Jahangirzadeh, A., Shamsirband, S., Aghabozorgi, S., Akib, S., Basser, H., et al., 2014, *Experimental and Numerical Investigation of The Effect of Different Shapes of Collars on The Reduction of Scour Around a Single Bridge Pier*, Neurocomputing: In Press, Kuala Lumpur.
- [5] Kumar, A., Kothyari, U.C., Rangarajub, K.G., 2012, *Flow Structure and Scour Around Circular Compound Bridge Piers—A Review*, *J. Hydro-Environment*, Res 6: 251–265, Roorkee.
- [6] Miller, J.W., 2003, *Model For The Time Rate Of Local Sediment Scour At A Cylindrical Structure*, Desertation, University of Florida, Florida,
- [7] Schneible, D.E., 1951, *An Investigation of The Effect of Bridge-Pier Shape on The Relative Depth of Scour*, Thesis, State University of Iowa, Iowa.
- [8] Triatmodjo, B., 2003, *Hidraulika II*, Beta Offset, Yogyakarta.