

DAFTAR PUSTAKA

- [1] ASTM D698 International, 2000, *Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort (12,400 ft-lbf/ft³ (600 kN-m/m³))¹*, US.
- [2] ASTM C-131 INTERNATIONAL, (2000). “*Standard Test Method for Resistance to Degradation of Small-Size Coarse Aggregate by Abrasion and Impact in the Los Angeles Machine¹*”.
- [3] ASTM C-136 INTERNATIONAL, (2000), “*Standard Test Method for Sieve analysis of Fine and Coarse Aggregates*”.
- [4] ASTM D-1883 INTERNATIONAL, (2000), “*Standard Test Method for CBR (California Bearing Ratio) of Laboratory-Compacted Soils*”.
- [5] ASTM D-2216 INTERNATIONAL, (2000), “*Standard Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass¹*”.
- [6] ASTM D-854 INTERNATIONAL, (2000), “*Standard Test Method for Specific Gravity of Soils Solids by Water Pycnometer¹*”
- [7] AASHTO T 193-99-2007, “*The California Bearing Ratio*”
- [8] DAS, Braja M, 1995. “*Principles of Geotechnical Engineering*”. Jakarta, Erlangga.
- [9] Iqbal, Ahmad Fauzi., 2019. “Pengaruh Pengurangan Dimensi *Mold* Terhadap Nilai CBR Material *Crushed Limestone* Pangandaran”. Skripsi.
- [10] Sahidin ,R.R., 2016 “Pengaruh Kadar Air Terhadap Degradasi Ukuran Butir Material *Crushed Limestone* Pasca Kompaksi”
- [11] SNI-1744-2012 “Metode Uji CBR Laboratorium”