IOP Conference Series: Earth and Environmental Science

Table of contents

Volume 1173 2023		
← Previous issue	Next issue ->	
3rd International	Conference on Disaster Management 29/09/2022 - 01/10/2022 Online	
Accepted papers received: 13 April 2023 Published online: 11 May 2023		

Open all abstracts

Preface			
OPEN ACCESS Preface: The 3 rd I	nternational Con	ference on Disaster Management (ICDM 2022)	011001
 Open abstract 	View article	[™] PDF	
OPEN ACCESS	ement		011002
 ✓ Open abstract 	View article	PDF	
Structures and	d Retrofitting		
OPEN ACCESS			012001
Flexural capacity	improvement of	the bamboo reinforced concrete beam with perpendicular pivot hooks	
A M Ummati, Micha	el, I P E Sarassantika	, G T Fanna, S Syuhada and A P Nasution	
 Open abstract 	View article	[™] PDF	
OPEN ACCESS			012002
The flexural strer	ngth of green foa	med concrete with polypropylene fiber	
K Al Qubro, A Sagga	aff and Saloma		
 Open abstract 	View article	PDF	
OPEN ACCESS	- (i . ()		012003
Snear capacities	of reinforced con	crete interior beam-column joints subjected to cyclic loading	
H Maulana, I Amal, '	W Iqbal, R Thamrin, .	Zaidir and R Kurniawan	
 Open abstract 	View article	ZPDF	
OPEN ACCESS			012004
The Numerical St	udy of The Need	for Transverse Reinforcement of a Spun Pile	
M Orientilize, W A P	rakoso, Y Lase, N W	Dessy and S Willie	
 Open abstract 	View article	[™] PDF	
OPEN ACCESS			012005
Cracks evaluation	n at a pier of a cu	rved box girder bridge during its balanced cantilever construction sequence	
N H Hidayat and H	Purnomo		
 Open abstract 	View article	PDF	
OPEN ACCESS			012006
Evaluation of seis Islamic Economic	smic vulnerability s and Business of	assessment building using rapid visual screening method: case study at the Facu I Islamic State Prof. KH. Saifuddin Zuhri University	lty of
M S H Pramesti, A V	Vidyaningrum and N	I S Hermanto	
 Open abstract 	View article	PDF	
OPEN ACCESS			012007
CI LIN ACCESS			012007



JOURNAL LINKS
Journal home
Journal scope
Information for organizers
Information for authors
Contact us
Reprint services from Curran Associates

Fauzan, M W Aulia, D A Nugraha M and Z A Jauhari View article Open abstract 012008 OPEN ACCESS Seismic assessment and retrofitting of the old URM railway station building in Padang City, Indonesia Fauzan, Z A Jauhari, G A Agista, N D Carol and Y S Putra Open abstract View article PDF **OPEN ACCESS** 012009 Numerical study of spun pile with steel jacket J Reagen, Y Lase, W A Prakoso and M Orientilize Open abstract View article **OPEN ACCESS** 012010 The Ratio of Cement and Sand from Lake Bingkuang as Aggregate to Create Foam Mortar 2,000 kPa D R Basri, E E Putri, B M Adji and A Hakam View article PDF **OPEN ACCESS** 012011 Comparative Analysis on Lateral Strength of Multi-Span RC Frame with Different Types of Infill Walls F Nugroho, Zaidir, J Tanjung and Maidiawati Open abstract View article PDF **OPEN ACCESS** 012012 Numerical Study of Castellated Beam with Stiffener - Case on Cantilever Structure S Haris, P K Sari and Masrilayanti Open abstract View article PDF **Tsunami and Seismic Engineering OPEN ACCESS** 012013 Spatial modelling of tsunami hazards and their exposure to settlements in Ambon City N Sugandhi, Supriatna, E Kusratmoko and H Rakuasa Open abstract View article PDF 012014 **OPEN ACCESS** Index active tectonic relative of Karangsambung geopark area, Central Java, Indonesia: assessment for developing geological disaster-based areas E Hidayat, D Muslim, Z Zakaria, H Permana and D A Wibowo Open abstract View article PDF **OPEN ACCESS** 012015 Post-disaster rapid assessment of Sunda Strait tsunami on 24th-25th December 2018 in the Regencies of Serang and Pandeglang, Province of Banten, Indonesia D A Tiwi, N Sudiana, Prihartanto, I Turyana, F Prawiradisastra, Q Zahro and Astisiasari Open abstract View article PDF **OPEN ACCESS** 012016 Study of Ground Motion Models Selection to the Concrete Frame Building Damage Probability using the 2006 Yogyakarta Earthquake Scenario Y Muntafi, N Nojima and I Ikramullah Open abstract View article PDF **OPEN ACCESS** 012017 The threat of tsunami debris due to non-permanent buildings in Cilacap City W Widiyanto, S N Purnomo and P B Santoso Open abstract View article PDF **OPEN ACCESS** 012018 Prediction of shelter needs based on simulation results of evacuees choosing evacuation facilities due to a potential tsunami earthquake in Padang, Indonesia Purnawan and E Kharisma Open abstract View article

OPEN ACCESS

012019

Tsunami current	and its impact or	n inundation depth in the coastal areas of West Sumatra – Indonesia	
D Daoed, M Syukur	and P S Ariya		
 Open abstract 	View article	PDF	
Geotechnical	Engineering		
OPEN ACCESS			012020
The influence of	helix diameter co	onfiguration on helical pile bearing capacity	
- Open abstract			
• open ubstruct			
OPEN ACCESS The influence of R Yuliet, A L Silvy, A	various paramete . Hakam, Fauzan, M I	ers of physical and mechanical properties on susceptibility to liquefaction of sand Mera and S Syuhada	012021 ly soils
 Open abstract 	View article	₽DF	
OPEN ACCESS			012022
A Comparison of Data in Jakarta	1-D S-wave Velo	city Profile Resulting from Microtremor Array Method and Lithology Profile from	Borehole
Mohamad Ridwan,	Asdani Soehaimi and	d Rio Alcanadre Tanjung Moechtar	
 Open abstract 	View article	₱ PDF	
OPEN ACCESS Placement of gen O C Pattipawaej	otextile tubes as o	coastal management of way hawang seashore area at Bengkulu Province	012023
 Open abstract 	View article	党 PDF	
OPEN ACCESS Analysis of clay i Andriani, H G Putra	mprovement as s , R Yuliet, R Maulana	ubgrade using Palm Oil Fuel Ash (Pofa) and S P Marel	012024
 Open abstract 	View article	[™] PDF	
OPEN ACCESS Clayshale stabiliz M F R Hasan, I Z Ut → Open abstract	zation using activ ama, A F A Razzak, A TView article	e natural lime to increase the shear strength of soil A Salimah and P A M Agung PDF	012025
OPEN ACCESS Rock slope stabil A P Martireni, K Sug • Open abstract	lity assessment us gianti, K Hermawan, a ≣View article	sing kinematic analysis at Gunung Batu, Lembang, West Java, Indonesia A Tohari, S Wibawa and E Soebeowo 陸PDF	012026
OPEN ACCESS Hydraulic gradie R A M Putra, D Prat	nt analysis on em iwi, A D Putra, E P W	Ibankment dam foundation associated with internal erosion ahono, D I Kusumastuti and A Fitri	012027
 Open abstract 	View article		
OPEN ACCESS Comparative Ana Yelvi, W A Prayoga,	alysis of Riverban W M Fachmi, A Salir	ks Retrofitting Planning Using Strauss Pile and Ground Anchor nah, Y Setiawan and M Hazmi	012028
 Open abstract 	View article	Z PDF	
OPEN ACCESS Understanding c P P Andika, A Tohar • Open abstract	if flow liquefactio i, T Yudistira, E Soeb ≣ View article	n in Lolu Village based on seismic refraction tomography method owo and J Arifin PDF	012029
OPEN ACCESS			012030
Liquefaction pot A Tohari, E Soebow → Open abstract	ential analysis for o, S Wibawa, K Herm Twiew article	r Palu City based on CPT method nawan and O F Saputra	0.2000
OPEN ACCESS			012031

OPEN ACCESS

Spatial and Temporal Analysis Prediction of Landslide Susceptibility Using Rainfall Infiltration and Grid-based Slope Stability Methods in West Bandung area of West Java-Indonesia

Koko Hermawan, Khori Sugianti, Antonina Martireni, Nugroho Aji Satrio and Yunarto

 Open abstract View article PDF

OPEN ACCESS

Effect of wet - dry cycles on CBR value and grain size distribution particle on compacted residual tuff soil S Syuhada, A H Muzakky, R Kurniawan, E T Utami and J Hayati View article PDF Open abstract **OPEN ACCESS** Slope stability analysis at coal mining sites in Central Kalimantan H Prabowo, E Barlian, N Syah and A T Sastra PDF **OPEN ACCESS** Liquefaction Mitigation Analysis Using Vertical Drain H Novasari, A Hakam and Andriani Open abstract View article PDF Water and Resources Engineering **OPEN ACCESS**

Application of X-Band rainfall radar data-based on soil water index for sediment Disaster monitoring in Boyong River (BO-D6) H R D and A Syarifudin Open abstract View article PDF

OPEN ACCESS An investigation of the changing patterns of rainfall in the Indravathi subbasin utilizing the Mann-Kendall and Sen's slope methods

Istijono Bambang, Subbarayan Saravanan, Nagireddy Masthan Reddy and Devanantham Abijith

 Open abstract View article PDF

OPEN ACCESS	012037
Activating an Adequate Management & Effective Emergency Unit for The Water Supply in The Armed Conflicts Zone	S
T M Alnajar, A Fitri, W Almadhoun, M S N Hadie, F C Ros, A E Kabeel and S Z H Shah	
✓ Open abstract Invite ✓ PDF	
OPEN ACCESS	012038
Analysis of extreme wind wave based on weibull and fisher tippett I (gumbel) distribution	
D Pratiwi, R Pratama, R A M P, A Fitri and F Lestari	
✓ Open abstract	
OPEN ACCESS	012039
Analysis of drainage network capacity in Rawa Jaya Area, Ilir Timur I, Palembang	
S Nisumanti, R Baniva and Afrizal	
✓ Open abstract	
OPEN ACCESS	012040
Adsorption using fly ash from stam power plants for acid mine drainage treatment	
S Siswati, H Pratama and M Giatman	
◆ Open abstract ■View article PDF	
OPEN ACCESS	012041
Performance Index of Anai I Irrigation-Area, Padang Pariaman	
Junaidi, Radhiatul Ulfa Jf and Mas Mera	
✓ Open abstract	
OPEN ACCESS	012042

Detection of flood inundation in serayu watershed using landsat-8 and sentinel-2 satellite imagery

Suroso, A Zikri, P B Santoso and Ardiansyah

 Open abstract View article PDF

OPEN ACCESS

Effectiveness analysis of East Sunter polder system for flood control management using HEC-HMS & HEC-RAS software

012043

012032

012033

012034

012035

012036

A Novrima and E Anggraheni		
✓ Open abstract	[™] PDF	
OPEN ACCESS		012044
Enhanced digital water level mea	surement for irrigation channel	012011
J A Loekito, R Y Tallar, O Pattipawaej, M	C Sutandi, T O Sihombing, P P Yapinus, J Chandra, M Tanubrata, H Lesmana, L Karsten et al	
◆ Open abstract	[™] PDF	
OPEN ACCESS		012045
Backwater flow analysis due to th	e construction of the check dam series on Aie Dingin River using HEC-RAS	
Open abstract Interview and F Arsyad	[™] PDF	
Transportation and Logisti	cs	
OPEN ACCESS		012046
Effects of COVID-19 on transport	ation services and travel behaviour in Malaysia	
L Gungat, D R Deh and E E Putri		
✓ Open abstract IIIView article	Z PDF	
OPEN ACCESS	n a than an a	012047
Management and the Indicators	n path parameters based on the requirements of indonesia National Agency of Disas of the Global Walkability	ter
F Rifwan, Yosritzal, Purnawan and Yossy	afra	
✓ Open abstract	₿PDF	
OPEN ACCESS		012048
Public Preferences of Using Publi Activity Restrictions Policy in Pad	c Transport During the <i>Covid-19</i> Pandemic and the Implementation of Level 3 Comm ang City	unity
Yosritzal, Titi Kurniati and Jihan Meiriza	Putri	
✓ Open abstract	[™] PDF	
OPEN ACCESS		012049
Accessibility Towards West Suma	tra Tourism Area	
Jihan Melasari, Purnawan, Yosritzal and	Yossyafra	
✓ Open abstract	Z PDF	
OPEN ACCESS		012050
Development of Traffic Delay and	Queue Metamodel on Landslide Zone Based on Simulation Using VISSIM	
 ✓ Open abstract	₽DF	
Understanding Disaster M	anagement	
OPEN ACCESS	analysis of flood prope area using remote sensing data and machine learning in Male	012051
Raya, East Java, Indonesia	analysis of nood profic area using remote sensing data and machine learning in mark	ing
M I Hariyono, D Ramdani, F E S Silalahi	A A Kurniawan, N Indriasari and M Buswari	
Open abstract Invite A straight of the straight of th	ZPDF	
OPEN ACCESS		012052
Population distribution analysis i	n Banda Aceh City for tsunami disaster risk reduction	
I Amri, R R Alami and A Serlia		
✓ Open abstract	₿PDF	
OPEN ACCESS		012053
Upstream Brantas Watershed ma	nagement strategies for flood mitigation (a review: Batu District)	
D A Handayani, A Kurniadi and F Bahar		
	™PDF	
OPEN ACCESS		012054
Disaster management and its imp	portance: a review paper of Dakshina Kannada and Kodagu districts, Karnataka, India	
M C Jayaprakash, D Venkat Reddy and	B Istijono	

◆ Open abstract
 □
 ▼View article
 ▼
 PDF
 ■

OPEN ACCESS Development of post-d	lisaster reha	bilitation and reconstruction information system	012055
T A Sundara, E Usada, H Sa	putra, L Arief	and M Hamidi	
	ew article	PDF	
OPEN ACCESS The pattern of material Putranesia, T Ophiyandri, F • Open abstract	I supply cha A Ismail and ew article	in in post-disaster reconstruction: a case study in Indonesia's disaster-prone area B Hidayat PPDF	012056
Landfilling as individua	al adaptation	n for coastal flooding (<i>Rob</i>) countermeasures in North Central Java	012057
 Open abstract ■Vie 	ew article		
OPEN ACCESS A study of community	slope risk an	nd awareness in Penang, Malaysia	012058
 Open abstract ■Vie 	ew article		
		_	
OPEN ACCESS The Importance of Villa Virana Fatwa Nurmala, Bert • Open abstract	age Resilien ton Suar Pelita ew article	ce Assessment in Village Based Programs to Support Regional Resilience I Panjaitan and Adi Subiyanto PPDF	012059
Strengthening Sus	tainability	y Development	
OPEN ACCESS			012060
Numerical Modelling o	of Constructo	ed Wetland using Software HYDRUS 2D	
✓ Open abstract	ew article	PDF	
			012061
Strategy for improving Jakarta	Green Ope	n Space (RTH) based on community participation in reduce the risk of flood disaster	in
P Salsabila, S Maarif and D	A P Sari		
 Open abstract	ew article	PDF	
OPEN ACCESS Estimating the Cost of 2	Strauss Pile	Retaining Wall Works Using the Cost Significant Method	012062
 ✓ Open abstract 	ew article		
OPEN ACCESS The Role of the Govern	ment of Ria	u Provincial in Dealing with Forest and Land Fires	012063
 ✓ Open abstract	ew article		
Enhancing Framew	vork for S	ustainability	
OPEN ACCESS Village resilience to tsu	ınami hazar	d: a Desk Research on the west-coastal villages of the Regency of Serang, Province of	012064
D A Tiwi, D Ganesha, N A A	Akhirianto, A P	Putra, R P Umbara, A F Shomim and Astisiasari	
◆ Open abstract	ew article	PDF	
OPEN ACCESS			012065
A conceptual framewor housing reconstruction	rk for imple projects	menting lean construction and building information modeling (BIM) in post-disaster	512003
A Syaputra and A D Raras	satı	Rode	
	Cw article		
			012066

Structural mitigation of rob flood disaster through mangrove forest conservation in Indonesia coastal areas

Improving Le	esson Learnt i	n Disaster Management	
OPEN ACCESS			01206
Utilizing informa	ation technology	towards reducing forest and peatland fire risk in Riau Province, Indonesia	
R J Eklou, I D K K W	/idana and Suwito		
 Open abstract 	View article	PDF	
OPEN ACCESS			01206
Community-bas during the covid	ed disaster risk re I-19 pandemic	eduction efforts in facing the threat of abrasion disasters at Bungin Beach, Beka	si Regency
S Fathoni, S Sutisna	a and M Supriyatno		
 Open abstract 	View article	[™] PDF	
OPEN ACCESS			01206
Potential debris	flow after eartho	uake in Mount Talamau Pasaman district and West Pasaman district	
F Bari, B Istijono, R	Yuhendra, A Hakam	ı, M Noer and T Ophiyandri	
 Open abstract 	View article	PDF	
OPEN ACCESS			01207
Analyzing the in flooding in Chim	npact of commur nanimani District,	ity-based approaches on disaster preparedness to the risk of tropical cyclone in Zimbabwe	duced
W Rangarirai, C Ma	rnani and A Rahma	t	
 Open abstract 	View article	₽PDF	
OPEN ACCESS			01207
Identification of	Lean Implement	ation in the Post-Disaster Housing Reconstruction	
D M Octavia, T Opł	niyandri, A Suraji and	d B Hidayat	
 Open abstract 	View article	[™] PDF	
OPEN ACCESS			01207
Underground-ca "Gua Pandan," E	aves connectedne ast Lampung Reg	ess preview using the geoelectrical profiling method as an effort to revive natura gency	al tourism in
R M Antosia, H H A	kbar, N A Santoso,	I A Putri, B A Farishi and H C Natalia	
 Open abstract 	View article	PDF	
OPEN ACCESS			01207
The capacity of l	Polyurethane Spo	onge to Adsorb Nitrate, Ammonium, and Phosphate	
T Edwin, M Mera, P	S Komala and Zuka	rnaini	
 Open abstract 	View article	PDF	
OPEN ACCESS			01207
Junior high scho	ol students prep	aredness toward earthquake in urban and rural areas in Pesisir Selatan	
R Salsabila, A R Alfi	an and A Rahman		
 Open abstract 	View article	PDF	
OPEN ACCESS			01207
Vulnerability Ass	sessment of non-	engineered houses related to earthquake in West Pasaman District	
Rahmat Fadli Zakir,	Abdul Hakam, Bam	bang Istijono, Melinda Noer and Syafira Rahmadilla Hape	

IOPSCIENCE	IOP PUBLISHING	PUBLISHING SUPPORT
Journals	Copyright 2024 IOP Publishing	Authors
Books	Terms and Conditions	Reviewers
IOP Conference Series	Disclaimer	Conference Organisers
About IOPscience	Privacy and Cookie Policy	



Developing countries access

IOP Publishing open access policy

Accessibility

This site uses cookies. By continuing to use this site you agree to our use of cookies.

У 🗭 in 🕞 🎭 🔗 🛛 IOP Publishing

IOP Conf. Series: Earth and Environmental Science

Placement of geotextile tubes as coastal management of way hawang seashore area at Bengkulu Province

O C Pattipawaej¹

¹Civil Engineering Department, Universitas Kristen Maranatha, Jl. Prof. drg. Suria Sumantri, MPH No. 65, Bandung 40164, Indonesia

E-mail: olga.pattipawaej@eng.maranatha.edu

Abstract. Way Hawang Beach, one of coastal tourist attraction, located in Way Hawang Village, Maje, Kaur Regency, Bengkulu Province is suffering from erosion. The regular erosion speed is approximately 2 to 3 meters/year, taking the distance from Way Hawang coastline to West Sumatra Causeway which around 250 meters. Efforts to eradicate abrasion on Way Hawang Coast are mostly carried out using coastal protective structures. One of the breakwater structures that can reduce wave energy is geotextile tubes, which is a low-threshold breakwater structure. Geotextile tubes create a synthetic barrier along shorelines and beaches to help control erosion. Geotextile tubes placement plays an important role in the overall protection system performance. The geotextile tubes are simulated in the abrasion and accretion positions on the Way Hawang coast. The simulation results indicated that the position between abrasion and accretion are the most effective position to manage and to avoid erosion in Way Hawang coast's area at Bengkulu Province.

1. Introduction

One of the provinces in Indonesia is Bengkulu which is located on the southwest coast of Sumatra. The length of the coast is about 576 km, bordering the Indian Ocean in the western part of Bengkulu Province and has a 550 km long national road. This national road is called the West Sumatra Causeway which is the only land transportation route between districts in Bengkulu Province and is used to reach West Sumatra and West Lampung [1]. The function of the West Sumatra Causeway is very vital, heavy vehicles cannot be passed if this road is damaged and will significantly disrupt the economic acceleration of the Bengkulu population. Apart from being very important infrastructure used for traffic services, goods, agricultural products, mining, plantations and oil distribution, Bengkulu's population, the majority of whom are agrarian, trusts severely on agricultural products and requires land transportation via this national road [2].

This West Sumatra causeway is extremely defenceless to being eroded by ocean water starting from the Indian Ocean which takes very resilient hydrodynamics and sea waves to erode the road barriers. Coastal abrasion that erodes roads has a severe value, where the regular erosion rate is 2 meters/year and occasionally up to 3 meters/year [2]. Figure 1 shows the abrasion at South Kaur District, Bengkulu Province. Residents' settlements in the coastal area of South Kaur District, Kaur Regency are threatened with abrasion. The reason is that the distance from the beach to the road and residents' houses is only a few meters. This makes residents hope that the local government can immediately build the coastal protection structure. Some blisters have been managed by the Ministry of PUPR. However, abrasion remains to transfer to other parts of the coast, so a comprehensive clarification is desired to address this problem [3-7].

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1



1173 (2023) 012023

Figure 1. Abrasion at South Kaur District, Kau Regency, Bengkulu Province

Way Hawang Beach is approximately 250 meters away from West Sumatra Causeway. This tourist attraction is in Way Hawang, Maje, Kaur Regency, Bengkulu Province. Way Hawang coastal area is experiencing abrasions. Efforts to eliminate abrasion on the Way Hawang Coast are mostly carried out using coastal protective structures, including breakwater structures [8-10]. One of the breakwater structures that can reduce wave energy is geotextile tubes, which is a low-threshold breakwater structure. Geotextile tubes create a synthetic barrier used along shorelines and beaches to help control erosion (see Figure 2). Geotextile tubes placement shows a useful responsibility in the performance of the complete safety scheme [11]. In this study, geotextile tubes were simulated in the position of abrasion and sedimentation on the Way Hawang coast. The simulation results indicated that the position between abrasion and sedimentation was the most effective position to manage and to prevent abrasion in Way Hawang coast's area of Bengkulu Province.



Figure 2. Geotextile Tubes

2. Materials and Methods

2.1. The study area

Way Hawang Village is in Kaur Regency, Bengkulu Province. The latitude of Way Hawang is 4.8632° South and longitude is 103.4360° E. Figure 3 shows Way Hawang Village and coastal area which was taken from Google Earth platform [12] and Batu Jung is in the middle of Way Hawang Beach which is a tourist spot. The research site was in the coastal area of Way Hawang.

IOP Conf. Series: Earth and Environmental Science 1

1173 (2023) 012023

doi:10.1088/1755-1315/1173/1/012023



Figure 3. Way Hawang Village and coastal area from Google Earth Engine

2.2. The forecasting of wave height on Way Hawang Beach

Wind data used for wave forecasting is sea level data at the generation site. This data was gained from direct measurements above sea level or measurements on land near the forecasting setting which was then transformed into wind data at sea. The results of processing wind data collected from the Bengkulu wind recording station from 2011-2020, with statistical analysis data, were used to calculate the hour and direction of wind deception. The maximum wind comes from the South, directly from India Ocean.

The calculation of waves, generated by the wind, was done by hindcasting [14]. The basic principle of this method is to estimate the wave height and period calculated from wind data and effectively fetched using empirical methods. The maximum wind speed was used in the calculation, which was intended to analyse the extreme conditions of the waves. The visualisation of wave height [15] at Way Hawang Beach can be seen in Figure 4. The maximum wave height at Way Hawang Beach arises from the South directly from Indian Ocean.



Figure 4. Wave rose of Way Hawang coastal area

The design wave height is the wave height of a certain return period at the location of the coastal protection structure, where the wave has transformed during its propagation from the deep sea. The wave data used is the period and wave height which is the result of a 10-year wind data hindcasting process. Furthermore, extreme wave analysis was carried out in the form of various return periods for each direction [16] and the 50-year return period wave height will be modelled using SMADA software [17]. The design wave height is 6.39 m from the results of this wave transformation model.

Furthermore, tides are an oceanographic physical phenomenon that needs to be studied as an effort to understand the circulation pattern of seawater masses. This tidal parameter generally determines the movement of water from midday to daily period depending on the type of tide that occurs in these waters. From the observation results, tide measurements are also used to determine the water level elevation.

The Mean High-Water Level, Mean Sea Level, and Mean Low Water Level at Way Hawang Beach are 1.08, 0.72, and 0.35 meters, respectively.

2.3. Design of Geotextile Tubes

The design and location of geotextile tubes was determined based on wave data. The result of forecasting wave height for the 50-year return period stands $H_{50} = 6.39$ m; therefore, the wave height (*H*), wave period (*T*), and the wavelength in the deep waters (L_0) are obtained as follows:

$$H = 33\% H_{50} = 2.1 \text{ m}$$

$$T = 3.88 \sqrt{H} = 5.63 \text{ second}$$

$$L_0 = 1.56 T^2 = 49.52 \text{ m}.$$

Furthermore, the height of breaking wave is 2.4777 m at the depth of the breaking wave is 2.7255 m.

The coastal protection structure using sand-filled geotextile tubes material at Way Hawang Beach has dimensions of 2 m high, a base width of 4.2426 m and a cross-sectional area of 6.2575 m². The geotextile tubes can be seen in Figure 5, where P_h is the pressure caused by waves (a combination of hydrostatic pressure and dynamic pressure) and P_p is the passive pressure caused by water pressure behind the structure. The geotextile tubes structure is stable against overturning, shear forces, and soil bearing capacity; therefore, it is in a stable and safe condition.



Figure 5. Geotextile tubes at Way Hawang Beach

2.4. Numerical Modelling System of Shoreline Change

The initial position of Way Hawang's shoreline is firstly done as an input by making the grids at a certain distance accordance to the long coastline that will be simulated. Data on the position of the Way Hawang's shoreline can be acquired from Google Earth Pro engine to AutoCAD application [18]. The distance between the grids is 66.3 m with 86 grids as shown in Figure 6. Wave data is the result of daily wind data processing in the form of wind speed and direction using a hindcasting program. The wave parameters obtained are the period, height and direction of the incoming wave. The number of wave data generated in one year is 8760 data.



Figure 6. Grid of the Way Hawang Coastline

The prediction of shoreline change can be obtained using numerical method over a given period. A numerical model called GENESIS (GENEralized model for SImulating Shoreline change) [19], is used

3rd International Conference on Disaster Management	IOP Publishing	
IOP Conf. Series: Earth and Environmental Science	1173 (2023) 012023	doi:10.1088/1755-1315/1173/1/012023

to calculate shoreline changes caused mostly by sea wave. This model is based on the one-line theory, which assumes that the beach profile remains unchanged, thus allowing shoreline change to be uniquely described in terms of shoreline position. The central task of this model is to simulate the shoreline response to constructions situated on or near the shore. GENESIS generally means that a simple user interface allows the system to be affected in a variety of situations involving the number, location, and combination of coastal protection structures. If all the input data needed for shoreline change prediction is obtainable, then the program will run through the START file. All comments in the START file are filled in according to the existing input and as required by GENESIS. The START input is also carried out, for conditions without or with the geotextile tubes.

3. Results and Discussion

Due to wave load, the shoreline at Way Hawang beach has changed. Figure 7 presents the shoreline change at Way Hawang coastal area. It can be seen from Figure 7 that the abrasions occur at grid 10-30 and the accretions occur at grid 30-50.



Figure 7. Coastline change at Way Hawang Beach due to wave load without coastal protection structure

The next step is to analyse the position of the most effective geotextile tube structure in order to minimise the occurrence of changes in the Way Hawang coastline. Three plans for the placement of geotextile tube structures were analysed. The placement of the geotextile tube structure at the location of the occurrence of abrasion and sedimentation was based on the results of coastline change analysis without the presence of a coastal protective structure. The first location was geotextile tube structure placement on grids 10 to 30 (the occurrence of abrasion), the second location was on grids 30 to 50 (occurrence of sedimentation), and the third location was on grids 10-50 (occurrence of abrasion and sedimentation). Figure 8 shows the coastline change due to the placement of the geotextile tube structure on the Way Hawang coast.



Figure 8. Shoreline change due to wave load with and without geotextile tube structure

The results of shoreline changes without the presence of a coastal protective structure and shoreline changes with the placement of geotextile tube structures at three different locations show that the average width of the occurrence of abrasion or sedimentation is as follows,

1. Abrasion width 0.2184 m where there is no coastal protection structure

2. Abrasion width of 2.7021 m for placement of geotextile tube structures on the grids 10 to 30

3. Abrasion width of 2.3252 m for placement of geotextile tube structures on the grids 30 to 50

4. Abrasion width of 0.0373 m for placement of geotextile tube structures on the grids 10 to 50.

The most effective placement of geotextile tube structures at the Way Hawang Beach is on the grids 10 to 50.

4. Conclusions

Shorelines are certainly dynamic and abrasion cycles are often a significant feature of their ecological character. Winds, waves and currents have normal forces that simply transfer sand and unconsolidated soil in shore areas, so that the position of the coastline changes rapidly. Development in coastal areas can increase erosion problems; this necessitates a great deal of effort to manage the problem of shore erosion and to return coastal function, to adapt both short- and long-term transformations caused by human activities, natural disasters and sea level rise.

Way Hawang coastal area at Kaur Regency, Bengkulu Province is experiencing abrasions. Efforts to eliminate abrasion on the Way Hawang Coast are mostly carried out using coastal protective structures. Erosion problems are exacerbated when preventive measures (i.e. selection of hard or soft structures) are inappropriate, inappropriately planned, constructed, or maintained and if effects on nearby shores are not carefully assessed. The geotextile tubes were simulated in the position of abrasion and sedimentation at Way Hawang coastal area. The simulation results indicated that the position between abrasion and sedimentation are the most effective position to manage and to prevent abrasion in Way Hawang coast's area of Bengkulu Province. Further research is how to maintain and retrofit the geotextile tubes at the coastal area.

Acknowledgments

The author is very grateful to the Institute for Research and Community Service at Universitas Kristen Maranatha, Indonesia which has provided the grant funds.

References

- [1] Ministry of Public Works of Republic Indonesia 2015 Ministerial Decree No 290/KPTS/M/2015
- [2] Suwarsono, Supiyati and Suwardi 2011 Makara J. Technol. 15(1) 31
- [3] Davidson M A, Lewis R P and Turner I L 2010 Coast. Eng. 57(6) 620
- [4] Suresh P L and Sundar V 2011 J. Hidro-Environ Res. 5(3) 157
- [5] Kermani S, Boutiba M, Guendouz M, Guettouche M S and Khelfani D 2016 Ocean Coast. Manag. 132 46
- [6] Cappietti L and Simonetti I 2020 J. Coast. Res. 95 197
- [7] Karambas T V and Samaras A G 2021 J. Mar. Sci. Eng. 9 1108
- [8] Choi K, Kim J and Lee J 2016 J. Coast. Res. 75 1062
- [9] Setyandito O, Purnama A C, Yuwono N, Juliastuti and Wijayanti Y 2020 ComTech 11 19
- [10] Pranzini E, Anfuso G, Cinelli I, Piccardi M and Vitale G 2018 Water 10 1647
- [11] Tayade B R, Mahalingaiah A V. Gokhale N V and Kudale M 2015 Aquat. Procedia 4 190
- [12] Warnasuriya T W, Kuddithamby G and Sudheera S G 2018 Mar. Geodesy 41 1
- [13] Sundari T, Samra B and Saptono A B 2020 IOP Conf. Ser.: Earth Environ. Sci. 469 012017
- [14] Hadadpour S, Etemad-Shahidi A, Jabbari E and Kamranzad B 2013 J. Coast. Res. 65 237
- [15] Marinho B, Coelho C, Larson M and Hanson H 2018 J. Coast. Conserv. 22 475
- [16] Chairunnisa, Atiah S N and Wahyuni R 2019 Jurnal Teknik: Media Pengembangan Ilmu dan Aplikasi Teknik 18 08
- [17] Khosravil G, Majidi A and Nohegar A 2012 Int. J. Probab. Stat. 1 160
- [18] Yasmin N. 2019 Introduction to AutoCAD 2019 for Civil Engineering Application (KS: SDC Publications)
- [19] Hanson H 1989 J Coast. Res. 5(1) 1